



A·B·DICK.
FLUID DUPLICATOR
Spirit or Azograph®

model

210

*hand operated duplicator provides
top quality copies, in 1 to 5 colors, at
the lowest cost possible.*

SPECIFICATIONS

Can be used with Models 501, 502, and 503 stands.

Construction: Steel, Nylon, oilite, and sealed ball bearings. All parts of machine corrosion resistant.

Finish: Smooth, easy-to-clean finish.

Weight: 34 lbs.

Size: 29 $\frac{1}{2}$ " long, 18 $\frac{1}{2}$ " wide, 11 $\frac{1}{2}$ " high.

Dust Cover: Standard equipment.

Moistening System: Gravity air lock principle controls flow of fluid from tank to trough to wick to roller to paper. Tank is removable; fluid supply visible. Tank capacity is approximately 1 qt. Fluid control is completely automatic. Wick is easily accessible for cleaning and replacement. Impression Roller pressure is variable by means of a lever.

Maximum Duplicating Area: 8 $\frac{1}{2}$ " x 13 $\frac{5}{8}$ ".

Paper Sizes: 3" x 5" to 9" x 14".

Paper Weights: Sub. 16 to 110 lb. Index.

Feed Pressure Lever: Simplifies feeding of lightweight or heavyweight paper or card stock.

Feed Table: Scale on table permits easy, quick and accurate setting of parallel moving rails. Accommodates 125 sheets of Sub. 20 paper. Dual roll feed. Lateral adjustment. Lever raises and lowers feed rolls and corner separators simultaneously for quick, easy paper loading. Guide rails with dual corner separators.

Registration: Plus or minus 1/32".

Copy Adjustment: Raise or lower 1/2"; 1" overall.

Copy Delivery: Face up.

Receiving Tray: Adjustable backstop.

Counter: Reset type.

Maximum Master Size: 9" x 14".

Master Loading Lever: Identified with arrow and open-close positions. Scale on cylinder corresponds with scale on feed table.

Blockout Slot: On cylinder just above master clamp.